

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A media discharge device, comprising:
a support member;
a telescoping device supported by the support member via a joint structure that allows the telescoping device to rotate with respect to the support member with at least one degree of freedom, the telescoping device comprising a first member and a second member that moves with respect to the first member in an extending direction and a retracting direction during operation of the media discharge device; ~~and~~
a media discharge port provided on the telescoping device; and
a counterweight provided on the telescoping device;
wherein the joint structure is one of a gimbal joint and a universal joint.
2. (Original) The media discharge device of claim 1, further comprising an actuator that drives the second member in the extending direction and in the retracting direction.
3. (Original) The media discharge device of claim 2, wherein the actuator is selected from the group consisting of a hydraulic actuator, a gear-driven actuator and a threaded actuator.
4. (Currently Amended) A media discharge device, comprising:
a support member;
a telescoping device supported by the support member via a joint structure that allows the telescoping device to rotate with respect to the support member with at least one degree of freedom, the telescoping device comprising a first member and a second member

that moves with respect to the first member in an extending direction and a retracting direction during operation of the media discharge device;

a media discharge port provided on the telescoping device;

an actuator that drives the second member in the extending direction and in the retracting direction; and

a standoff sensor that is associated with the actuator and maintains a predetermined distance between the media discharge port and an object to which media is discharged.

5. (Currently Amended) The media discharge device of claim 4, wherein the standoff sensor comprises:

a sensor that detects a distance to ~~an~~ the object ~~to which media is discharged;~~
and

a controller that controls the actuator to drive the second member based on the detected distance and thereby maintain the predetermined distance between the media discharge port and the object.

6. (Original) The media discharge device of claim 5, further comprising an input device connected to the controller, the input device inputting a desired value corresponding to the predetermined distance.

7. (Original) The media discharge device of claim 6, wherein the input device is a user input device.

8. (Original) The media discharge device of claim 4, wherein the standoff sensor comprises:

a mechanical feeler that contacts the object; and

a switch, operatively connected to the mechanical feeler, that controls the actuator to drive the second member based on whether the mechanical feeler is in contact

with the object and thereby maintain the predetermined distance between the media discharge port and the object.

9. (Original) The media discharge device of claim 2, wherein the actuator includes a manual switch.

10. (Canceled)

11. (Canceled)

12. (Original) The media discharge device of claim 1, wherein the joint structure is freely manually manipulatable.

13. (Original) The media discharge device of claim 1, wherein the second member has one degree of freedom with respect to the first member.

14. (Original) A media discharge system, comprising:

the media discharge device of claim 1; and

a media reservoir connected to the discharge port by a media passage.

15. (Original) A media discharge system, comprising:

the media discharge device of claim 1; and

a semi-stationary object that holds the media discharge device.

16. (Currently Amended) A media discharge device, comprising:

a support member;

a telescoping device supported by the support member via a joint structure that allows the telescoping device to rotate with respect to the support member with at least one degree of freedom, the telescoping device being supported at only a single point, the telescoping device comprising a first member and a second member that moves with respect to the first member in an extending direction and a retracting direction during operation of the media discharge device; and

a counterweight provided on the telescoping device; and

a media discharge port provided on the telescoping device.

17. (Previously Presented) The media discharge device of claim 16, wherein the joint structure is one of a gimbal joint and a universal joint.

18. (Currently Amended) A media discharge device comprising:

a support member;

a telescoping device having a first end and a second end, the telescoping device being supported by the support member via a joint structure that allows the telescoping device to rotate with respect to the support member with at least one degree of freedom, the telescoping device being supported at only a single point and allowed to move in an extending direction and a retracting direction during operation of the media discharge device;

a media discharge port provided at the first end of the telescoping device; and

a counter weight provided near the second end of the telescoping device and suspended in mid-air during operation of the media discharge device.

19. (New) A media discharge device, comprising:

a support member;

a telescoping device supported by the support member via a joint structure that allows the telescoping device to rotate with respect to the support member with at least one degree of freedom, the telescoping device comprising a first member and a second member that moves with respect to the first member in an extending direction and a retracting direction during operation of the media discharge device; and

a media discharge port provided on the telescoping device;

wherein the joint structure is one of a gimbal joint and a universal joint and the joint structure is freely manually manipulatable.

20. (New) The media discharge device of claim 19, further comprising an actuator that drives the second member in the extending direction and in the retracting direction.

21. (New) The media discharge device of claim 20, wherein the actuator is selected from the group consisting of a hydraulic actuator, a gear-driven actuator and a threaded actuator.

22. (New) A media discharge device, comprising:

a support member;

a telescoping device supported by the support member via a joint structure that allows the telescoping device to rotate with respect to the support member with at least one degree of freedom, the telescoping device being supported at only a single point, the telescoping device comprising a first member and a second member that moves with respect to the first member in an extending direction and a retracting direction during operation of the media discharge device; and

a media discharge port provided on the telescoping device;

wherein the joint structure is freely manually manipulatable.

23. (New) The media discharge device of claim 22, wherein the joint structure is one of a gimbal joint and a universal joint.